

## RACK SUPPORTED FRIDGE

Model	Cu. ft. volume	Wall Thk	Cooler unit mounting	Integral floor	Wall material	Door type	Voltage	Total load BTU/H	Approx wt. (lb.)
Standard Refrigerator AIC	3,978	4"	Top	Option	Polyurethane	Rapid rollup	208-230/60/1	19,287	3,685
<p>Based on max ambient temperature of 35°C            Based on min. ambient temperature of -9°C            Supplied with integral digital thermometer            Available with automatic remote alerts and controls            Based on standard dimensions of 13' wide x 17' deep x 18' high. Final specifications will be based on your custom configuration, should it be different than this.            Floor: concrete            Temperature range to be confirmed in Technical Section of our quotation            Based on a safety factor of 8%</p>									

## RACK SUPPORTED FREEZER

Model	Cu. ft. volume	Wall Thk	Cooler unit mounting	Integral floor	Wall material	Door type	Voltage	Total load BTU/H	Approx wt. (lb.)
Standard Freezer AIF	3,978	4"	Top	Polyurethane	Polyurethane	Rapid rollup	208-230/60/1	22,555	4,185
<p>Based on max ambient temperature of max 35°C            Based on min. ambient temperature of min -9°C            Supplied with integral digital thermometer            Available with automatic remote alerts and controls            Based on standard dimensions of 13' wide x 17' deep x 18' high. Final specifications will be based on your custom configuration, should it be different than this.            Floor: Polyurethane            Temperature range to be confirmed in Technical Section of our quotation            Based on a safety factor of 8%</p>									